U.S. Patent Application No. 10/735,394

Reply to Office Action of May 16, 2007

Date: August 10, 2007

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims:

Claim 1 (currently amended): An inverted microscope having a U-shaped microscope

housing (1), on one limb (2) whereof is provided a housing attachment surface (3) for attachment

of a module, wherein said housing attachment surface (3) is parallel to the base of said inverted

microscope; and,

wherein said module (4) comprises a horizontally protruding base unit (5) having a horizontal

upper surface and a binocular tube (6) and a photo tube (7) individually attached to said

horizontal upper surface, with a photo device (8) placed on said photo tube (7) and wherein said

binocular tube (6) and said photo tube (7) are mutually exclusive and extend above said housing

attachment surface (3) when said module (4) is removably attached to said housing attachment

surface (3), and wherein from the position of looking into the binocular tube (6) an unimpeded

view of the specimen is permitted.

Claim 2 (previously presented): The inverted microscope as defined in Claim 1, wherein the

module (4) is embodied as a one-piece combination module (4; 5, 6, 7) and has on its underside a

module attachment apparatus (9) that is configured to be removably attached to the housing

attachment surface (3).

Attorney Docket No. LWEP:121US U.S. Patent Application No. 10/735,394

Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 3 (previously presented): The inverted microscope as defined in Claim 1, wherein the

vertical optical axis (10) of the observation beam bundle, extending in the one limb (2),

penetrates through a first optical deflection element (11) after entering the base unit (5), and then

passes through a first tube lens (12) arranged in the binocular tube (6), while the photo beam (13)

deflected at the optical deflection element (11), after passage through a second tube lens (14) and

after deflection at a second optical deflection element (15), enters the photo tube (7) with

attached photo device (8).

Claim 4 (previously presented): The inverted microscope as defined in Claim 1, further

comprising an optical deflection element (11) in said module and wherein the optical deflection

element (11) can be selectably brought into or out of the working position.

Claim 5 (previously presented): The inverted microscope as defined in Claim 1, wherein an

infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 6 (previously presented): The inverted microscope as defined in Claim 1, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

Claim 7 (original): The inverted microscope as defined in Claim 6, wherein the

eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the photo

tube (7) or photo device (8) have an HC correction.

U.S. Patent Application No. 10/735,394 Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 8 (previously presented): The inverted microscope as defined in Claim 2, wherein the

vertical optical axis (10) of the observation beam bundle, extending in the one limb (2),

penetrates through a first optical deflection element (11) after entering the base unit (5), and then

passes through a first tube lens (12) arranged in the binocular tube (6), while the photo beam (13)

deflected at the optical deflection element (11), after passage through a second tube lens (14) and

after deflection at a second optical deflection element (15), enters the photo tube (7) with

attached photo device (8).

Claim 9 (previously presented):

The inverted microscope as defined in Claim 3, wherein the

optical deflection element (11) can be selectably brought into or out of the working position.

Claim 10 (previously presented):

The inverted microscope as defined in Claim 8, wherein the

optical deflection element (11) can be selectably brought into or out of the working position.

Claim 11 (previously presented):

The inverted microscope as defined in Claim 8, wherein the

optical deflection element (11) can be selectably brought into or out of the working position.

Claim 12 (previously presented):

The inverted microscope as defined in Claim 2, wherein an

infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 13 (previously presented):

The inverted microscope as defined in Claim 3, wherein an

infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

U.S. Patent Application No. 10/735,394

Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 14 (previously presented): The inverted microscope as defined in Claim 4, wherein an

infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 15 (previously presented): The inverted microscope as defined in Claim 8, wherein an

infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 16 (previously presented): The inverted microscope as defined in Claim 9, wherein an

infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 17 (previously presented): The inverted microscope as defined in Claim 10, wherein

an infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 18 (previously presented): The inverted microscope as defined in Claim 11, wherein

an infinity beam exists in the region of an attachment surface (9a) of the module attachment

apparatus (9).

Claim 19 (previously presented): The inverted microscope as defined in Claim 2, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

Claim 20 (previously presented): The inverted microscope as defined in Claim 3, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

U.S. Patent Application No. 10/735,394 Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 21 (previously presented): The inverted microscope as defined in Claim 4, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

Claim 22 (previously presented): The inverted microscope as defined in Claim 5, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

Claim 23 (previously presented): The inverted microscope as defined in Claim 8, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

Claim 24 (previously presented): The inverted microscope as defined in Claim 9, wherein the

eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from those in

the photo tube (7) or photo device (8).

Claim 25 (previously presented): The inverted microscope as defined in Claim 10, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 26 (previously presented): The inverted microscope as defined in Claim 11, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 27 (previously presented): The inverted microscope as defined in Claim 12, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Attorney Docket No. LWEP:121US U.S. Patent Application No. 10/735,394

Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 28 (previously presented): The inverted microscope as defined in Claim 13, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 29 (previously presented): The inverted microscope as defined in Claim 14, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 30 (previously presented): The inverted microscope as defined in Claim 15, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 31 (previously presented): The inverted microscope as defined in Claim 16, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 32 (previously presented): The inverted microscope as defined in Claim 17, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 33 (previously presented): The inverted microscope as defined in Claim 18, wherein

the eyepieces (16a, 16b) of the binocular tube (6) have a different degree of correction from

those in the photo tube (7) or photo device (8).

Claim 34 (previously presented): The inverted microscope as defined in Claim 19, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

U.S. Patent Application No. 10/735,394

Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 35 (previously presented): The inverted microscope as defined in Claim 20, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 36 (previously presented): The inverted microscope as defined in Claim 21, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 37 (previously presented): The inverted microscope as defined in Claim 22, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 38 (previously presented): The inverted microscope as defined in Claim 23, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 39 (previously presented): The inverted microscope as defined in Claim 24, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 40 (previously presented): The inverted microscope as defined in Claim 25, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 41 (previously presented): The inverted microscope as defined in Claim 26, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

U.S. Patent Application No. 10/735,394 Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 42 (previously presented): The inverted microscope as defined in Claim 27, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 43 (previously presented): The inverted microscope as defined in Claim 28, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 44 (previously presented): The inverted microscope as defined in Claim 29, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 45 (previously presented): The inverted microscope as defined in Claim 30, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 46 (previously presented): The inverted microscope as defined in Claim 31, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 47 (previously presented): The inverted microscope as defined in Claim 32, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Claim 48 (previously presented): The inverted microscope as defined in Claim 33, wherein

the eyepieces (16a, 16b) have a periplan correction, and the eyepieces or TV adapters in the

photo tube (7) or photo device (8) have an HC correction.

Attorney Docket No. LWEP:121US U.S. Patent Application No. 10/735,394 Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 49 (previously presented): The inverted microscope as defined in Claim 3 wherein said passage through a second tube is parallel to said attachment surface.

Claim 50 (previously presented): The inverted microscope as defined in Claim 8 wherein said passage through a second tube is parallel to said attachment surface.

Claim 51 (currently amended): An inverted microscope comprising:

a U-shaped microscope housing (1), on one limb (2) whereof is provided a housing attachment surface (3) for removable attachment of a module, wherein said housing attachment surface (3) is parallel to the base of said inverted microscope, said module (4) comprises a protruding base unit (5) having a horizontal upper surface and a binocular tube (6) and a photo tube (7) individually attached to said horizontal upper surface, with a photo device (8) placed on said photo tube (7) and wherein said binocular tube (6) and said photo tube (7) are mutually exclusive and extend above said housing attachment surface (3) when said module (4) is removably attached to said housing attachment surface (3) and wherein from the position of looking into the binocular tube (6) an unimpeded view of the specimen is permitted;

said module (4) further comprising a movable optical deflection element (11) and a second optical element, said photo tube (7) in front of said movable optical deflection element and said binocular tube (6) behind said movable optical deflection element (11), and wherein said movable optical deflection element (11) reflects at least a portion of a light beam entering said module (4) in a first vertical direction into said photo tube (7) is reflected by said movable optical deflection element (11) in a horizontal direction when said movable optical deflection element (11) is in a working position, said at least a portion of said light is subsequently reflected by said second optical element in a second vertical direction into said photo tube (7) and said first vertical direction light beam entering said binocular tube (6) is substantially parallel to said at least a portion of said light beam entering said photo tube (7) second vertical direction.

Attorney Docket No. LWEP:121US U.S. Patent Application No. 10/735,394 Reply to Office Action of May 16, 2007

Date: August 10, 2007

Claim 52 (new):

The inverted microscope as defined in Claim 1 further

comprising:

a light beam; and,

said base unit further comprises a module changing apparatus, and first and second optical elements, wherein said base unit is removably attached to said U-shaped microscope housing by connecting said housing attachment surface to said module changing apparatus, said light beam enters said base unit in a first vertical direction through said module changing apparatus, said light beam is split into an imaging beam and a photo beam by said first optical element, said imaging beam passes through said first optical element and enters said binocular tube, said photo beam is reflected by said first optical element in a horizontal direction towards said second optical element, said photo beam is subsequently reflected by said second optical element in a second vertical direction through said photo tube, and said first and second vertical directions are substantially parallel.